

**Zonal Office:Gonda** 

### **NOTICE INVITING TENDER**

# Sub: COMPETITIVE QUOTATION FOR INTERIOR FURNISHING WORK OF JAMTHARA BRANCH DISTT GONDA UNDER GONDA ZONE

Competitive sealed quotations are invited in the prescribed format from the contractors who are already empanelled with bank executed interior furnishing of nationalized Banks in last three years.

Formats of Quotations document is enclosed for submission of interior furnishing work of **JAMTHARA branch**, Distt- Gonda. Full details and tender document are available in Bank's website <a href="https://www.indianbank.in">www.indianbank.in</a> or can be obtained from Zonal Office Gonda. Duly filled tenders should be submitted as per following schedule:

1	Issue of Tender Document	From 05.12.2024 to 20.12.2024
2	Submission of Tender	On or before 20.12.2024 up to 5:00PM
3	Opening of Tender	On 21.12.2024 at 04:00 PM
4	Estimated cost of work	Rs 5.76 Lacs
5	Date of Commencement	7 Days from the date of issue of letter awarding the job
6	Time of Completion	20 days
7	Defect Liability Period	12 Months
8	Earnest Money	Rs.5000/- in form of DD/IOI in favour of Indian Bank payable
	·	at Gonda.
		*Firms registered with MSME/NSIC with valid certificate
		issued by GOI are exempted from submitting EMD along
		with Tender.
9	Liquidated Damages for delay	Rs.2000/- per day subject to Max. of 10 % of accepted
		contract amount.
		(If the work is not completed to the satisfaction of the
		Employer within the stipulated period the contractor shall be
		bound to pay to the employer a sum equivalent to Rs. 2000/-
		per day subject to ceiling of 10% of the accepted contract
		amount by way of liquidated damages and not as penalty during which the work remains un-commenced or unfinished
		after expiry of the completion date.
10	Payment Terms	Neither any advance nor any Interim payment will be made.
10	1 ayınıcını Tennis	
		i Pavineni wili ne mane on salistacioty combletion of the ion i
		Payment will be made on satisfactory completion of the job on the basis of actual measurements. Income tax will be
		on the basis of actual measurements. Income tax will be
		, , , , , , , , , , , , , , , , , , ,
		on the basis of actual measurements. Income tax will be deducted as per the rules. Retention money 10% will be
		on the basis of actual measurements. Income tax will be deducted as per the rules. Retention money 10% will be deducted the bill and to be released after 12 months from
11	Document to be attached with	on the basis of actual measurements. Income tax will be deducted as per the rules. Retention money 10% will be deducted the bill and to be released after 12 months from the date of virtual completion provided no defects is observed during this period.  Manager completion Certificate, Manufacture Certification
11	Document to be attached with the Bill Retention Money	on the basis of actual measurements. Income tax will be deducted as per the rules. Retention money 10% will be deducted the bill and to be released after 12 months from the date of virtual completion provided no defects is observed during this period.

The Bank will not be bound to accept the lowest tender and reserves the right to accept or reject any or all the tender without assigning any reason whatsoever. Late/delayed tender shall not be accepted after due date and time of submission of tender.

# **CLIENT**

## **INDIAN BANK**

ZONAL OFFICE GONDA- Premises Department Bahraich Road, Near Roadways Bus stop Gonda Uttar Pradesh-271001

### WORK /PROJECT

# PROPOSED INTERIOR FURNISHING WORK OF JAMTHARA BRANCH-DISTT GONDA UNDER GONDA ZONE

# COMPETITIVE QUOTATION FOR INTERIOR FURNISHING AT ABOVE PROJECT

Tender Issued to
M/S
Address
Contact No
Tender Issued on :
Last Date ofSubmission : 20.12.2024
Signature of the Contractor
<u>seal</u>

**Zonal Office: GONDA** 

### NOTICE INVITING TENDER

# Sub: COMPETITIVE QUOTATION FOR INTERIOR FURNISHING WORK OF JAMTHARA BRANCH DISTT GONDA UNDER GONDA ZONE

#### **General terms & Conditions:-**

I) Sealed quotation should be addressed to The Zonal Manager, Indian Bank, Zonal Office Gonda and super scribed name of Work Interior Furnishing of **JAMTHARA Branch**, at Village Jamthara, new railway crossing Post Kaudia Bazar, Distt- Gonda and should reach before 5:00 p.m. on 20.12.2024 at Zonal Office Gonda.

### Mailing Address:

The Zonal Manager, INDIAN BANK Zonal Office Gonda Bahraich Road,Near Roadways Bus Stop, Gonda-271001(U.P)

- No quotation will be accepted after 5:00 pm on 20.12.2024 and quotations will be opened on 21.12.2024 at 4:00 pm unless otherwise informed.
- 3) The quotations will remain valid for a period of 3 months from the date of opening.
- 4) Bank reserves the right to accept or reject any or all the quotations accept part of any tender, entrust the entire work to any contractor or divide the work to more than one contractor (item wise) without assigning any reason to do so or giving any explanation. The rates quoted by the contractors will help well for bifurcation and no compensation will be paid on this account.
- 5) At the time of submission every quotation must be accompanied by IOI/ Demand Draft for an amount of Rs.5000/- in favour of INDIAN BANK payable at Gonda towards EMD. Any quotation which is not accompanied by EMD will be summarily rejected. \*Firms registered with MSME/NSIC with valid certificate issued by GOI are exempted from submitting EMD along with Tender.
- 6) Contract should quote rates in figures as well as in words.
- 7) All erasures and alterations made must be attested with the initials of tenderers. No overwriting is permitted.
- 8) The EMD of the unsuccessful bidders will be returned within 45 days from the date of opening the tender.
- 9) Joint tenders shall not be considered. Conditional tenders quoted by the contractor are liable to be rejected.
- 10) No escalation in the rates will be allowed under any circumstances.
- 11) On receipt of the intimation from the bank of the acceptance of his quotation, the contractor should submit his acceptance within 3 days if the successful contractor/ tenderer fail to undertake the work within 7 days after work allotment, the MMD will be forfeited and acceptance of his tender may be withdrawn.
- 12) The rate quoted in the tenders shall be inclusive of all materials as required and shall be inclusive of all charges of scaffoldings, lifting, tools and plants, freights/ transportation, labour conditions and fluctuations in rates of excise duty, octroi, GST, VAT, Excise Duty, service tax and any other taxes or expenditure of carrying out the works.
- 13) The Agency is advised to inspect and examine the sites and satisfy himself as to the condition prevailing at sites and its surrounding extent of work, scope and conditions under which the work is to be executed. The contractor shall also satisfy himself about the accessibility to the premises.
- 14) The agency shall submit the offer which satisfies each and every condition laid dawn in this notice, failing which the tender will be liable to be rejected. Conditional bids shall not be considered and will be out rightly rejected in the very first instance.
- 15) Work will be completed within the period of 20 days from the date of issue of tender or work order whichever is earlier. If the work be not completed to the satisfaction of employer within the stipulated period, the contractor will be bound to pay to the Employer a sum equivalent to Rs.2000/- per day subject to ceiling of Max 10% of the accepted contract amount by way of liquidated damages and not as penalty during which the work remains uncommenced or unfinished after expiry of the completion date. The contract may be rescind by giving one week notice incase work is not executed as per specification and as per time schedule given in tender document.
- 16) The liquidated damages as mentioned in the Notice inviting tender may not be enforced if the contractor applies for extension of time mentioning the genuine reasons for extension. If an extension of time of completion of the work is sought on the grounds of having unavoidable hindrances in his execution or any other ground, the contractor shall apply in writing to the Zonal Manager, Zonal Office BALRAMPUR with full details of the circumstances which is causing such an extension. Extension of time in days will be granted by the bank if it is proved that the contractor is not at fault for extending the work beyond stipulated date of completion. At the decision in this regard taken by the Bank shall be binding to the contractor.
- 17) The successful contractor is bound to carry item of work necessary for completion of job even though the same are not included in the schedule of quantity. Rates of extra item will be derived from quotation. In case the rates do not exist in quotation and extra item is not similar to the quoted item, then the rates will be worked out on actual cost of material and labour, any other expenditure for completing that work plus 15% towards contractors profit and overheads.
- 18) The work shall be carried out in such a way that, there is least disturbance to the staff of Bank. Contractors are required to organize the work in such a way that workings of staff and officers/executives of Office are not affected. Contractor is required to take adequate Care during progress of work to protect belongings. In case any damage, contractors at their own cost shall make the same good.
- 19) The contractor must co-operate with other contractors appointed by the bank so that entire work shall proceed smoothly and to the complete satisfaction of the Bank.

- 20) Contractor will arrange necessary tools and plants for completing own work at their cast. In case of any accident the total responsibility will be on the contractor. Contractors are required to submit time schedule of work. After completion of work, cleaning of floors, walls etc are to be done on daily basis to the satisfaction of Branch Head / engineer-in-charge. After completion of jobs, the site shall be cleared of all rubbish malba /debris etc in all respect and handover the site in proper manner on completion of the work.
- 21) No advance will be paid. Payment will be released on satisfactory completion of job and submission of bills. Retention Money @10% will be deducted from the bill and to be released after twelve months from the data of virtual completion provided no defects is observed during the period.
- 22) In case of non-completion or delay in completion of work or removal of defects in time, the bank shall be free to appoint another agency to get the job done at contractors risk and cost.
- 23) The contractor will attend to all the defects noticed during defect liability period. If the contractor fails to attend the defects these defects will be got rectified by the bank and the expenditure incurred on this account will be recovered from security deposit / retention money.
- 24) The work shall be got approved by the Architect / engineer and the contractor shall rectify any bad workmanship pointed out at any stage and remove from the site all the rejected materials immediately at his own cost.
- 25) The contractor shall acquaint himself with the site conditions making his own arrangements for storing of materials at site, lift, cartage etc. at his own risk and safety.
- 26) The Contractor shall make adequate arrangement for watch and ward of material and shall ensure the safety, breakage and any theft of material fixed or unfixed by him or the other sub contractors. The bank shall not be liable for any sort of loss incurred.
- 27) The contractor shall be responsible for application of labour laws, compensation for injury and accident to person, whether employed by him or his sub-contractor.
- 28) The contractor shall ensure that the workmen employed by him for the execution of work are suitably covered against Workmen Compensation Act and that all liabilities arising out of Workmen's .
- 29) Compensation Act, ESIS and other legislative enactment applicable to such works and workmen shall be to the contactor's account and responsibility.
- 30) Civil, Interior Furnishing and Electrical Works will be carried out as per Bank's standard drawing / specifications and to the entire satisfaction of the bank.
- 31) The contractor shall inform the bank, well in time, to check measurements of anywork, which is likely to be hidden before covering
- 32) Income tax at me prevailing rates will be deducted at source from contractor's bill and will be deposited with I.T.O. as per rules.
- 33) Any extra work or item can only be started by contractor after obtaining written approval from the Zonal Office. Item executed without prior approval from the Zonal Office will not be considered for payment.
- The quantities mentioned in the schedule of quantities are approximate. Payment will be made on the actual work done by the contractors. However the contractor should not deviate the quantity without Banks permission.
- 35) The Bank has the right to alter the nature of work and to add or omit any items of work or to have the option of the same carried out departmentally or otherwise and such alterations or variations shall be carried out without prejudices to the contract.
- 36) The Bank has the right to terminate the contact if the contractor abandons the work or fails to commence the work in time, or fails to abide by the terms & conditions of the contract.

I have read and understood all the instructions/conditions given above and I have taken into account the above instructions/conditions while quoting the rates.

Date:	(Signature of the Contractor)
Place:	Seal

SNO. DESCRIPTION UNIT QTV. RATE AM  SUSPENDED FALSE CEILING  1.1 FALSE CEILING (GYPSUM BAORD)  Providing and fixing Gypsum false ceiling as per drawing including of providing and fixing Gypsum false ceiling as per drawing including of providing and fixing Gypsum false ceiling as per drawing including of providing and fixing Gypsum false ceiling as for Li, perimeter channel (MF-6A) of size 0.50mm thick having one flange of 19.6mm and another flange shall be of size 29.6mm and a web of 26.6mm along with perimeter of ceiling, server fixed to the beam to the required curvature with nylon sleeves and screws at not exceeding 610mm centers. Then suspending GL intermediate channel (MF-7) of size 45mm, 0.9mm thick with two flanges of 15mm each bent to the required curvature by cutting both its flanges. Suttable bracing to be provided where ever the flanges are cut with 0.9mm GL. Flat and nuts and bolts at specific positions and thereafter at 1220mm centers with ceiling angle of whith 25mm x 10mm x 0.50mm thick fixed to soffit with GL. cleats and steel expansion fasteners as per specification of India gypsum at a distance of 20° c/c both ways complete with 12.5mm board and all necessary perimeter channels etc.  The joints to be properly mended with paper tapes and gypsum compound all complete. The boards are to be jointed and finished which includes filling and finishing the tapered and square edges of the boards with jointing compound and finishing the tapered and square edges of the boards with jointing compound and finishing the tapered and square edges of the boards with jointing compound and finishing the tapered and square edges of the boards with jointing compound and finishing the tapered and square edges of the boards with jointing compound and finishing and finishing the tapered and square edges of the boards with jointing compound and finishing and finishing the tapered and square edges of the boards of paper decided for the stable for the stable for special paper and the paper decided for the stable for the s		B.O.Q OF REFURNISHING WORK FOR INDIAN BANK BRANCH AT JAM	THARA -	GONDA(U	P)	
1.1 SUSPENDED FALSE CEILING  1.1 FALSE CEILING (GYPSUM BAORD)  Providing and fixing Gypsum false ceiling as per drawing including of providing and fixing GL. Frame work shall comprise of GL. perimeter channel (MF-6A) of size 0.50mm thick having one flange of 19.6mm and another flange shall be of size 29.6mm and a web of 26.6mm along with perimeter of ceiling, serve fixed to the beam to the required curvature with nylon sleeves and screws at not exceeding 610mm centers. Then suspending GL intermediate channel (MF-7) of size 45mm, 0.9mm thick with two flanges of 15mm each hent to the required curvature by cutting both its flanges. Suitable bracing to be provided where ever the flanges are cut with 0.9mm GL. Flat and nuts and both sat specific positions and thereafter at 1220mm centers with ceiling angle of width 25mm x 10mm x 0.50mm thick fixed to soffit with GL. deats and steel expansion fastners as per specification of india gypsum at a distance of 20° c/c both ways complete with 12.5mm board and all necessary perimeter channels etc.  The joints to be properly mended with paper tapes and gypsum compound and finishing the tapered and square edges of the board's with jointing compound and finishing the tapered and square edges of the board's with jointing compound and finishing the tapered and square edges of the board's with jointing compound and finishing with the paper of the bard with jointing compound and finishing with the paper of the bard with jointing compound and finishing with the paper of the bard with jointing compound and finishing with the paper of the bard with jointing compound and finishing with the paper of the bard with jointing compound and finishing with the paper of the bard with jointing compound and finishing with the paper of the bard with jointing compound and finishing with the paper of the bard with the application paint (foller finish) of approved shade and make shall be applied. The rate should include the full complete of the paper of the bard with the paper of the bard with the pa	A	SCHEDULE - 'A' (FURNISHING WORK)				
1.1 FALSE CEILING (GYPSUM BAORD)  Providing and fixing Gypsum false ceiling as per drawing including of providing and fixing GJ. Frame work shall comprise of GJ. perimeter channel (MF-6A) of size 0.50mm thick having one flange of 130mm and another flange shall be of size 29.6mm and a web of 26.6mm along with perimeter of ceiling, screw fixed to the beam to the required curvature with myon sleeves and screws at not exceeding 610mm centers. Then suspending GJ. intermediate channel (MF-7) of size 45mm, 0.9mm thick with wood flanges of 15mm each hent to the required curvature by cutting both its flanges of 15mm each hent to the required curvature by cutting both its flanges of 15mm each hent to the required curvature by cutting both its flanges of 15mm each hent to the required curvature by cutting both its flanges of 15mm each hent to the required curvature by cutting both its flanges of 15mm each hent to the required curvature by cutting both its flanges of 15mm each hent to the required curvature by cutting both its flanges of 15mm each hent to the required curvature by cutting the flanges of 15mm each hent to the required curvature by cutting of 15mm and 15mm his flanges of 15mm his	S.NO.	DESCRIPTION	UNIT	QTY.	RATE	АМТ
Providing and fixing Gypsum false ceiling as per drawing including of providing and fixing GJ. Frame work shall comprise of GL. perimeter channel (MF-6A) of size 0.50mm thick having one flange of 19,6mm and another flange shall be of size 29.6mm and a web of 26.6mm along with perimeter of ceiling, screw fixed to the beam to the required curvature with ylon sleeves and screws at not exceeding 610mm centers. Then suspending GL intermediate channel (MF-7) of size 45mm, 0.9mm thick with two flanges of 15mm each bent to the required curvature by cutting both its flanges. Suitable bracing to be provided where ever the flanges are cut with 0.9mm GL. Flat and nuts and boths at specific positions and threather at 1220mm centers with ceiling angle of width 25mm x 10mm x 0.50mm thick fixed to soffit with GL. cleats and steel expansion fasteners as per specification of India grypsum at a distance of 20° c/c both ways complete with 12.5mm board and all necessary perimeter channels etc.  The joints to be properly mended with paper tapes and gypsum compound all complete. The boards are to be jointed and finished which includes filling and finishing the tapered and square edges of the boards with jointing compound and fiber tape suitable for Gypsum board. A layer up to of 3.00mm thickness of Veneer Plaster is applied followed by two coats of topsor with jointing compound and fiber tape suitable for Gypsum board. A layer up to of 3.00mm thickness of Veneer Plaster is applied followed by two coats of topsor with jointing compound and fiber tape suitable for Gypsum board. A layer up to of 3.00mm thickness of Veneer Plaster is applied followed by two coats of topsor with jointing compound and fiber tape suitable for Gypsum board. A layer up to of 3.00mm thickness of Veneer Plaster is applied followed by two coats of topsor the sale is a followed by the followed by followed by the followed	1	SUSPENDED FALSE CEILING				
and fixing G.I. Frame work shall comprise of G.I. perimeter channel (MF-GA) of size 0.50mm and a one flange of 19 (bmm and another flange shall be of size 29.6mm and a web of 26.6mm along with perimeter of ceiling, screw fixed to the beam to the required curvature with ylon sleeves and screws at not exceeding 610mm centers. Then suspending G.I. intermediate channel (MF-7) of size 45mm, 0.9mm thick with two dianges of 15mm each bean to the required curvature by cutting both its flanges. Suitable bracing to be provided where ever the flanges are cut with 0.9mm G.I. Flat and nuts and bolts at specific positions and thereafter at 1220mm centers with ceiling angle of width 25mm x 10mm x 0.50mm thick fixed to sofflit with G.I. cleats and steel expansion fasteners as per specification of India gypsum at a distance of 20° c/c both ways complete with 12.5mm board and all necessary perimeter channels etc.  The joints to be properly mended with paper tapes and gypsum compound all complete. The boards are to be jointed and finished which includes filling and finishing the tapered and square edges of the boards with jointing compound and fiber tape suitable for Gypsum board. A layer up to of 3.00mm thickness of Veneer Plaster is applied followed by two coats of topcoat (primer) at the face of board to give smooth seamless finish. 2 or more coats of plastic emulsion paint (roller finish) of approved shade and make shall be applied. The rate should include the full completion of the ceiling. At the time of handing over the site all necessary repairing work to be considered if required. The work to be completed as per specification, approval of the bank. No Drop or designif(fr any) will be considered as extra measurement it will be considered flat ceiling. (Only plan area to be measured for payment). No extra apprant will be made for the cutting of light points, stain glass,cove lighting etc. The measurement will be taken in one level, rate should include the drops also, no extra amount will be paid for the drops.  Providing a	1.1	FALSE CEILING ( GYPSUM BAORD)				
complete. The boards are to be jointed and finished which includes filling and finishing the tapered and square edges of the boards with jointing compound and fiber tape suitable for Gypsum board. A layer up to of 3.00mm thickness of Veneer Plaster is applied followed by two coats of topcoat (primer) at the face of board to give smooth seamless finish. 2 or more coats of plastic emulsion paint (roller finish) of approved shade and make shall be applied. The rate should include the full completion of the ceiling. At the time of handing over the site all necessary repairing work to be considered if required. The work to be completed as per specification, approval of the bank. No Drop or design(if any) will be considered as extra measurement it will be considered flat ceiling. (Only plan area to be measurement it will be considered flat ceiling. (Only plan area to be measurement it will be considered flat ceiling. (Only plan area to be measurement will be taken in one level, rate should include the drops also, no extra amount will be paid for the drops.  FALSE CEILING (ARMSTRONG CEILINGS – FINE FISSURED MICROLOOK EDGE WITH SILHOUETTE GRID (BLACK REVEAL)  Providing and fixing false ceiling system manufactured by M/s. Armstrong World Industries using hot dipped galvanized steel section, rotary stitched main tee of size 15mm x 42 mm, having 0.35 mm gauge at every 600 mm. c/c. and wall angle of size 19 x 19 mm, having 0.35 mm gauge at every 600mm. c/c. and wall angle of size 19 x 19 mm, having 0.35 mm gauge fixed to the periphery of the wall. The above grid is suspended at every 600mm c/c. in both directions using 2.0 mm. thick pre-straightened Gl wire laying FINE FISSURED MICROLOOK WITH SILHOUETTE GRID BLACK REVEAL) ceiling tiles manufactured by M/s. Armstrong World Industries, of size 600mmx60mmx15mm having NRC 0.55, Light reflectance of >84% (WT), thermal conductivity k = 0.052-0.057 W/mOK, flumidity Resistance of 99%, having Fire Performance CLASS O/ CLASS I (BS 476), surface having 3 coats of white paint with Fin		and fixing G.I. Frame work shall comprise of G.I. perimeter channel (MF-6A) of size 0.50mm thick having one flange of 19.6mm and another flange shall be of size 29.6mm and a web of 26.6mm along with perimeter of ceiling, screw fixed to the beam to the required curvature with nylon sleeves and screws at not exceeding 610mm centers. Then suspending G.I. intermediate channel (MF-7) of size 45mm, 0.9mm thick with two flanges of 15mm each bent to the required curvature by cutting both its flanges. Suitable bracing to be provided where ever the flanges are cut with 0.9mm G.I. Flat and nuts and bolts at specific positions and thereafter at1220mm centers with ceiling angle of width 25mm x 10mm x 0.50mm thick fixed to soffit with G.I. cleats and steel expansion fasteners as per specification of India gypsum at a distance of 2'0" c/c both ways complete with 12.5mm board and all	Sq.Ft.	440.00		
Providing and fixing false ceiling system manufactured by M/s. Armstrong World Industries using hot dipped galvanized steel section, rotary stitched main tee of size 15mm x 42 mm web height, having 0.36 mm gauge at every 600 mm centre to centre maximum and rotary stitched cross tee of size 15 mm x 42 mm, having 0.33 mm gauge at every 600 mm. c/c. and wall angle of size 19 x 19 mm., having 0.35 mm gauge fixed to the periphery of the wall. The above grid is suspended at every 600mm c/c. in both directions using 2.0 mm. thick pre-straightened Gl wire laying FINE FISSURED MICROLOOK WITH SILHOUETTE GRID(BLACK REVEAL) ceiling tiles manufactured by M/s. Armstrong World Industries, of size 600mmx600mmx15mm having NRC 0.55, Light reflectance of >84% (WT), thermal conductivity k = 0.052-0.057 W/m0K, Humidity Resistance of 99%, having Fire Performance CLASS 0 / CLASS 1 (BS 476), surface having 3 coats of white paint with Fine Fissured, back of the tile duly sanded and finished with a coat of protective paint over the formed grid complete.(Branch & ATM).		complete. The boards are to be jointed and finished which includes filling and finishing the tapered and square edges of the boards with jointing compound and fiber tape suitable for Gypsum board. A layer up to of 3.00mm thickness of Veneer Plaster is applied followed by two coats of topcoat (primer) at the face of board to give smooth seamless finish. 2 or more coats of plastic emulsion paint (roller finish) of approved shade and make shall be applied. The rate should include the full completion of the ceiling. At the time of handing over the site all necessary repairing work to be considered if required. The work to be completed as per specification, approval of the bank. No Drop or design(if any ) will be considered as extra measurement it will be considered flat ceiling. (Only plan area to be measured for payment). No extra payment will be made for the cutting of light points, stain glass, cove lighting etc. The measurement will be taken in one level,				
Industries using hot dipped galvanized steel section, rotary stitched main tee of size 15mm x 42 mm web height, having 0.36 mm gauge at every 600 mm centre to centre maximum and rotary stitched cross tee of size 15 mm x 42 mm, having 0.33 mm gauge at every 600 mm. c/c. and wall angle of size 19 x 19 mm., having 0.35 mm gauge fixed to the periphery of the wall. The above grid is suspended at every 600mm c/c. in both directions using 2.0 mm. thick pre-straightened GI wire laying FINE FISSURED MICROLOOK WITH SILHOUETTE GRID(BLACK REVEAL) ceiling tiles manufactured by M/s. Armstrong World Industries, of size 600mmx600mmx15mm having NRC 0.55, Light reflectance of >84% (WT), thermal conductivity k = 0.052-0.057 W/m0K, Humidity Resistance of 99%, having Fire Performance CLASS 0 / CLASS 1 (BS 476), surface having 3 coats of white paint with Fine Fissured, back of the tile duly sanded and finished with a coat of protective paint over the formed grid complete.(Branch & ATM).	1.2					
THE ALL ALL ALL ALL ALL ALL ALL ALL ALL AL		Industries using hot dipped galvanized steel section, rotary stitched main tee of size 15mm x 42 mm web height, having 0.36 mm gauge at every 600 mm centre to centre maximum and rotary stitched cross tee of size 15 mm x 42 mm, having 0.33 mm gauge at every 600 mm. c/c. and wall angle of size 19 x 19 mm., having 0.35 mm gauge fixed to the periphery of the wall. The above grid is suspended at every 600mm c/c. in both directions using 2.0 mm. thick pre-straightened GI wire laying FINE FISSURED MICROLOOK WITH SILHOUETTE GRID(BLACK REVEAL) ceiling tiles manufactured by M/s. Armstrong World Industries, of size 600mmx600mmx15mm having NRC 0.55, Light reflectance of >84% (WT), thermal conductivity k = 0.052-0.057 W/m0K, Humidity Resistance of 99%, having Fire Performance CLASS 0 / CLASS 1 (BS 476), surface having 3 coats of white paint with Fine Fissured, back of the tile duly sanded and finished with a coat of	Sq.Ft.	404.00		
THE ALL ALL ALL ALL ALL ALL ALL ALL ALL AL		DARTHIANG WORK				
4.4 FULL / LOW HEIGHT SOLID PARTITION / DOOR /UPS	1	PAKIIIIUNS WURK				
		FILL / LOW HEIGHT SOLID PARTITION / DOOD /UPS	0 -	040		

	Full ht. Solid Partition up to ceiling only WITH LOUVRE: Providing and fixing solid partition, the framing shall made out of aluminium hollow section of 65mm x 37mm size 1.5mm thick of JINDAL / INDAL as internal frame structure placed horizontally & vertically at max distance of 2'-0" x 2'-0" center to center. Fixing 6 mm thick commercial ply on both sides with 1.0mm thick laminate on top of approved shade with groove pattern as per instructions of Architect. The rate shall include the cost of providing skirting of 100mm wide lined with 1mm thk laminate and providing & fixing a border at top of 100mm wide lined with 1mm thk laminate complete. Laminate Should be considered up to two or three color combination. The edge beadings with steam beach wood should be finished with melamine polish if required, frame work above false ceiling done shall not be measured but contractor may factor it while quoting there rates as measurment up to false ceiling lvl			
	The rate inclusive of providing & fixing of required flush door of $37mm$ thick approx. with 1.0mm th.laminate both side with steem beech wood chowkhat of size $75mm \times 65mm$ approx and Item includes Heavy-duty SS ball bearing butt hinges $100 \times 5.5 mm$ (4 Nos. per shutter) with screws etc.The shade of laminate finish to be got approved from Bank All as per the design and instructions Bank.			
	Note:-For the purpose of payment partition shall be measured including the area of door/door frames up to false ceiling heaight.			
	Framework shall be regidly secured to floor, bottom of slab & exisitng walls at 2'- $0$ " c/c with dash fasteners.			
4.0	Full / low height Glazed partition manager cabin	C E:	150.00	
1.3	Same as of Solid ht. partition, providing 8mm thick Modi/saint Gobin float glass above 1'-0" / 3'-0" & up to 7'-0" fixed with steam beech wood beading of finished size 1 1/2" X 1" all along the edge. All edge-to-edge glass joint to be machine cut and polished and sealed with silicon sealant. joint shall be located strictly as shown in the drawing. All exposed woodwork to be mealamine polished. Item includes frosted/striped/designer glass film of 3m, Avery Dennison or equivalent ( basic rate of Flim Rs. 50/ Sq.ft. ) on existing glass as per manufacturer's specifications. All as per the design and instruction Bank.	Sq.Ft.	170.00	
1.4	7' Height Glazed partition in Cash cabin	Sq.Ft.	100.00	
	Same as of Solid ht. partition , providing Aluminium grill jalli above 1'-0" / 3'-0" & up to 7'-0" fixed with steam beech wood beading of finished size 1 $1/2$ " X 1" all along the edge. All exposed woodwork to be mealamine polished. All as per the design and instruction Bank.			
1.5	Low Height Semi Glazed Partition Counter	Sq.Ft.	65.00	
	Same as above but of Low height as per design including 10mm Toughened glass with edges polished to be used. All other specs are same as of above, Edges of the partition to be covered with 3" X 1.5" Steam beech wood duly melmine polished moulding. 38mm thick flush door: <b>wicket gate</b> also shall be included for a measurement. All as per the design and insturction bank.			
1.6	Front Glazeing cash cabin & trophy stand in manager cabin	Sq.Ft.	30.00	
	Providing & fixing 10mm thick toughened clear float glass to shape for front side of the cash counters including cutting the holes and providing & fixing TW beading polished and tinted to approved shade. (including SWO/Chief Cashier front Glass).			
1.7	Aluminium grill on the ceiling of Cash cabin	Sq.Ft.	75.00	
2	DOOR & ACCESSORIES			
2.1	Main Entrance Door with Fixed Glazing	Sq.Ft.	75.00	
	Providing and fixing aluminium entrance doors with 12mm floatglass (3M frosted sticker) as/design with top & bottom section of 45 by 90mm, 2mm thick section of hindalco/Jindal anodized in approved colour with 25 micron anodizing along with SS C shaped handles of kitch or equivalent make along with floor spring of hemco/everite make. The item also includes door lock completed to the satisfaction of the architect.			

2.2	Supplying and fixing of Dorma/GEZE Dline / Hardwyn/Godrej or approved equivalent Door Closer for wooden door for Cashier.	Nos	5.00	
2.3	Supplying and fixing of mortice door lock of hardwyn make HML-480 Lock Body 304 Stainless Stell. (in BM Cabin , Store room 0. Cash cabin shall be Godrej Night latch.	Nos	5.00	
2.4	Supplying and fixing of door stopper SS Grade 304, HESSF-2C hardwyn make.	Nos	6.00	
3	WORKING COUNTER			
3.1	CASH COUNTERS	Rft.	9.00	
	Providing and fixing Chief Cash Counter in split-levels @ 2'-6" (height 750mm) & 18" (1140mm) with 2'-6" & 15" wide each respectively. Upper levels having 12mm thick frosted toughened glass (i/c taxes and transportation). Edges of 18" wide counter shall be 12mm thick frosted toughened glass. Lower tier shall be made of 19 mm thick ply wood finished in 1.5mm thick laminate. Exposed edge having steam beech wood edging of size 1 ½" x 1". Vertical face shall have 12mm thick frosted toughened glass as per requirement of design. All exposed surfaces shall be finished with 1.0mm thick laminate of approved shade and colour.			
	1 no. prefabricated metal computer key board tray including drawer slides 12.5" x 22" tray with 14" telescopic slides including L – brackets for securing to the table top. Chest of drawers (size 1'-4" x 2'-0" x 2'-5") made of 19mm thick commercial ply wood having three drawers finished with 1.0mm thick Laminate on all sides. Each drawer shall have locking system and 6" long S.S. brushed finished handle, drawer slides etc. of approved make. All exposed edges of ply wood sealed with Steam beech wood beading of size $^{1}\!\!\!/^{x}$ x $^{3}\!\!\!/^{x}$ . All beading and exposed wood shall be melamine polished and the Internal surfaces shall be .75 mm thick laminate. Item includes readymade metal powder coated CPU trolley, grommet, footrest for each seat. All complete as per approval and instructions of the Architect / employer. The rate also include providing and fixing painting a foot rest using hard wood 100 x 25mm size 1st class seasoned country frame.			
	Payment will be made only on the centerline measurement. The rate shall include the cost of providing skirting of 100mm wide lined with 1.0mm thk laminate and providing & fixing a border at top of 100mm wide lined with 1.0mm thk laminate comlpete. the Internal surfaces shall be .75 mm thick laminate.			
2.2	RUNNING COUNTER	D&	17.50	
3.2	Providing and fixing staff counter/SWO in split-levels @ 2'-6" (750 mm) & 3'1" with 2'-6" (750 mm) & 9" wide each respectively. Upper levels having 1 mm thick laminate with 19 mm thick commercial ply top. Lower tier shall be made of 19mm thick ply wood and finished in 1 mm thick laminate. Working top having steam beech wood edging of size 1 ½" x 1". Vertical face shall have 19 mm thick commercial ply over pine wood framework as per requirement of design. All exposed edges of ply wood sealed with Steam beech wood beading of size ¼" x ¾". All exposed surfaces shall be finished with 1.0mm thick laminate of approved shade.	Rft.	17.50	

	The item includes Chest of drawers (size 1'-4" x 2'-0" x 2'-5") made of 19mm thick commercial ply wood having One drawers at top and a storage cabinet below having shutters of 19mm thick ply wood finished with 1.0mm thick Laminate on all sides. 1 no. prefabricated metal computer key board tray including drawer slides 12.5" x 22" tray with 14" telescopic slides including L – brackets for securing to the table top for each seat. All beading and exposed wood shall be melamine polished and the Internal surfaces shall be .75 mm thick laminate. Item includes 1'-3" high 12mm thick toughned glass above upper tier and readymade metal powder coated CPU trolley, grommet, foot rest for each seat. All complete as per approval and instructions of the Architect / employer.The rate also include providing and fixing painting a foot rest using hard wood 100 x 25mm size 1st class seasoned country frame. Payment will be made only on the centerline measurement.			
	1.0mm thk laminate and providing & fixing a border at top of 100mm wide lined with 1.0mm thk laminate comlpete.			
4	TABLE & FURNITURE			
4.1	MANAGER TABLE ( Size:- 6'-0" x 3'-0") ht. 2'-6"	Nos	1.00	
	Providing and fixing tables made out of 19 mm thick commercial ply over hard wood frame work finished with 1 mm thick laminate of approved shade. Top having steam beech wood edging of size 2" x 1 ¾". 10mm thick clear float glass with beveled edges shall be provided on the finished to 19mm thk Comm.ply wood of approved make cladded with 1mm thk. laminate( color with vertical grain) as per design in all visible areas. All the exposed edges to be covered with wooden steam beech lippings and mouldings duly malamine polish. The drawers to be made out of 19mm thk ply wood with 1.0 mm laminate finish in the front, and bottom to be made out of 6mm plywood and it should play in drawer sliding telescopic channels. The inside of the drawer shall be .75 mm thick laminate. & Table back side wil be 1mm laminate. A leg rest to be provided duly polished made out of 3"x2" Wooden Section.The rate inclusive of providing &fixing wooden cabinet to suit the DVR for size 2'X6"X1'9" or as per the requirements)			
	A shutter to be made by 19mm ply wood cladded with1.0mm laminate. The necessary locks handles to be provided in each drawers and shutters. 3" x 1/2" wooden skiriting to be provided in all visible areas duly polished. The necessary wire managers(SS) to be provided on the tables and provision for lights to be kept if required in the front of the table. All the exposed areas to be duly malamine polished The work to be completed as per design and approval of the Bank. The table should have key board tray and CPU Trolly to be Modular. All as per the design and instructions Bank the Internal surfaces shall be .75 mm thick laminate.  Officer TABLE ( Size:- 5'-0" x 2'-6") ht. 2'-6" as above specification without			
4.2	glass top	Nos	0.00	
5	STORAGE & SIDE UNIT			
5.1	Side and Back Unit			
	Providing and fixing Side Unit/ Back unit 400 mm depth made out of 19mm ply wood finished with 1.0mm laminate in all exposed areas and top shall be 1 mm thick . The drawers to be made out of 19mm commercial plywood and cladded with 1.0mm laminate and bottom made out of 6mm comm ply duly painted in matching tone and it should play on drawer sliding channels . The shutters to be made out of 19mm commercial ply wood and should play on drawer sliding castors on powder coated channels. The necessary locks , handles, etc to be provided . 3" x1/2 wooden skirting to be provided duly polished as per matching tone all along the visible areas . Inside of the unit shall be .75 mm thick laminate. in matching tone . All the exposed edges of the boards/ply woods to be coverd with woden lippings/mouldings duly polished all complete. The work to be completed as per approval and specification of the Architect.	NO	1.00	
5.2	Storage	Sq.Ft.	100.00	
J.2	<u> </u>	54.1 t.	100.00	

	Providing and fixing Full /Low height Cabiner400mm deep made out of 19mm thk plywood finished with 1.0mm laminate in all exposed areas . The Shutter to be made out of 19mm ply wood in the front cladded with 1.0mm laminate( color, vertical grain) . and bottom made out of 6mm plywood duly painted in matching tone and shelves 19mm thk comm ply wood to fixed inside storage. The shutters to be made out of 19mm ply wood . The necessary locks , handles, etc to be provided . 3" x1/2 wooden skiritng to be provided duly polished as per matching tone all along the visible areas . Inside of the unit shall be .75 mm thick laminate finish . All the exposed edeges of the boards/plywoods to be coverd with wooden lippings/mouldings duly polished all complete.All as per the design and instructions Bank.			
6	OTHER MISCELLANEOUS ITEMS			
6.1	PIN UP / NOTICE BOARD			
0.1	Providing and fixing soft board with necessary framework with 12mm BWR plywood on top 12 jolly board to be fixed finished with fabric @Rs80, with necessary mouldings duly polished along the periferi. All as per the design and instructions Bank.	NO	1.00	
	WRITING LEDGER & Cheque & sugestion box		1.00	
6.2	Providing and fixing writing ledge as per design minium 5 ft length made out	NO	1.00	
	19mm comm. board with necessary grove patterns with 1.0mm laminate. 10mm thk machine polished glass to be provided on top of the writing ledge. Small boxes to be made out of 12mm comm. ply to be made on top of the writing ledge finished with 1.0 mm laminate, inside enamel painted and rate should be included providing fixing of sugestion box & Cheque deposit box as per approval of bank. The work to be completed as per design and approval of the architect.			
6.3	Main Electrical Panel Cabinet			
	Providing and fixing of DB Shuttering formed of 12mm thk plywood wood on 12mm thick Gypsum board (fire Proof) with finsih as per Item no 1 for inside and out side shutters finished with laminate on outer surface with SS (4Nos) louvre perforation and necessary hardware, hinges etc complete as per details. All as per the design and instructions Bank.	Sq.Ft.	35.00	
6.4	Shutter boxing for ROLLING SHUTTER			
	P & F shutter boxing made of 19 m.m. phenol bonded ply IS 303 grade including hatch fir pulling down & up the rolling shutter. The box to be laminated with aluminium composite panel of 3.0 m.m. completed to the satisfaction of architect. Front surface will be taken for measurement only.	Sq.Ft.	60.00	
6.5	Column panelling Branch			
	Fabricating and fixing wall/column paneling, the framing shall made out of aluminium hollow section of 65mm x 37mm size 1.5mm thick of JINDAL / INDAL at spacing not exceeding 600mm bothways (horizontal and vertical). Paneling framework to be secured to wall surface/column surface.Paneling framework to be clad on one side with 9mm thick ply finished with 1.0mm thk laminate including skirting of 100mm high & 12mm x 12mm groove at skirting level. All as per the design and instructions Bank.	Sq.Ft.	100.00	
6.6	Customer Table - (4'-0" X 2'-6")			
	Providing and making a table of over all size of top as mentioned above. It shall consist of 3/4" thk. Comm. Ply top as per design (double edge on outer edge with 1 1/2" thk half moulding on the edges) supported on 3/4" thk. Comm. Ply verticals.supported on wooden base (as designed by the architect). Suitable wooden moulding as architect design with mellamine shall be provided to the edge of the top. All external surfaces to be finished in 1 mm laminate.	No.	1.00	
6.7	ROLLING BLINDS	Sq.Ft.	150.00	

	Providing and fixing Roller blinds of approved design and shade by the Architect,incl all std fittings as per manufacturer's specification. The work to be completed as per specification and approval of the architect. (approved brand Vista, Hunter Dogulus)			
6.80	PAINTING PLASTIC PAINT	Sq.Ft.	700.00	
	Applying 2 Coat putty with primer and Providing and applying Plastic emulsion paint (asian) of approved make and shade on walls including scrapping off, preparing the base & applying 3 or more coats of approved make, color and shade to give an even and smooth surface on new work including necessary scaffolding, coat of cement primer etc. all complete as per direction of Bank. (only banking hall.)			
6.9	Applying 2 coat of Plastic emulsion paint (asian) of approved make and shade on walls including scrapping off, preparing the base ect color and shade to give an even and smooth surface on new work including necessary scaffolding, coat of cement primer etc. all complete as per direction of Bank. (Other than banking hall.)	Sq.Ft.	3100.00	
7	ENAMEL PAINT	Sq.Ft.	600.00	
	Providing & applying 1st quality oil paint of approved make, quality & shade. The rate shall include scrapping, levelling & preparing the surface with primer quote.			
7.1	EXTERIOR GRADE CEMENT PAINT			
a.	UP TO 10 FEET HEIGHT	Sq.Ft.	500.00	
	Providing & applying exterior grade cement paint of approved quality, make & shade, after scrapping the surface with wire brush & then applying (minimum) 3 coats of paint as directed by Bank / Architects.			
	GRAND TOTAL FOR FURNISHING (A)			
	* GST EXTRA AS APPLICABLE			